Bohnenkamp Moving Professionals



Hints and features:

- The Security TR 603 is a professional tyre for use on car trailers.
- The tyre is reinforced by additional casing plies and offers very good stability.

Dæk 155 R 13 C, TR603 8 PR, 91 / 89 N (90 / 88 R), TL, M+S Security

Product-No.: 18345277

Technical Information:

Product number	18345277
Tyre Size	155 R 13 C
R / D	Radial
TL/TT	TL
LI / SI	91 / 89 N (90 / 88 R)
PR	8
Profile	TR603
Manufacturer	Security
Specification	M+S
Recom. Rim	4.50
Width mm	157
Outer diameter mm	578
Static radius mm	270
Rolling circumference mm	1751
Payload in kg at kph (1)	615 / 140
Payload in kg at kph (2)	600 / 170
Inflation pressure bar	4,50
Weight kg	5,7
Rolling resistance	D
Wet grip	С
Rolling noise DB	72
Rolling noise level	В
Certified	ECE 54, ECE 117
M+S	M+S
Nennbreite [mm]	155
LI 4	88
Commercial van mark	С
Profilsymmetrie	symmetrisk

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.