

WINDPOWER
Get Your Job Done



Dæk 7.50 R 16, WGC 08
14 PR, 122 / 118 L, TT, 3PMSF
inkl. slange + fb, TR 77 A, VA/HA/TR, Windpower

Product-No.: 10466388

Technical Information:

Product number	10466388
Tyre Size	7.50 R 16
R / D	Radial
TL / TT	TT
LI / SI	122 / 118 L
PR	14
Profile	WGC 08
Manufacturer	Windpower
Specification	3PMSF, Slange + vulstbånd
Recom. Rim	6.00G
Permissible rim	5.50F, 6.50H
Width mm	214
Outer diameter mm	807
Static radius mm	375
Rolling circumference mm	2161
Payload in kg at kph (1)	1500 / 120
Inflation pressure bar	7,70
Weight kg	33,2
Rolling resistance	E
Wet grip	B
Rolling noise DB	73
Rolling noise level	B
Stud height mm	13,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nennbreite [Zoll]	7.50
Profilsymmetrie	symmetrisk

Hints and features:

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.