





Hints and features:

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Dæk 265 / 70 R 19.5, WGC 28 18 PR, 143 / 141 J, TL, 3PMSF VA/HA/TR, Windpower

Product-No.: 10466434

Technical Information:

Product number	10466434
Tyre Size	265 / 70 R 19.5
R/D	R
TL / TT	TL
LI / SI	143 / 141 J
PR	18
Profile	WGC 28
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	7.50
Permissible rim	8.25
Width mm	258
Outer diameter mm	877
Rolling circumference mm	2675
Payload in kg at kph (1)	2725 / 100
Inflation pressure bar	8,30
Weight kg	41,10
Rolling resistance	E
Wet grip	В
Rolling noise DB	74
Rolling noise level	В
Stud height mm	17,5
Certified	ECE54, ECE117
M+S	M+S
3PMSF	3PMSF
Nennbreite [mm]	265
Querschnittsverhältnis	70

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.