

WINDPOWER
Get Your Job Done



Hints and features:

- Modern, heavy-load trailer tyre for local, regional and long-haul transport.
- Its special rubber compound provides lower rolling resistance and increased mileage.
- Its wet grip has been improved, as has its water dispersion capabilities thanks to a stone-repellent sipe in the tread base.
- Reduced heat generation.

Dæk 245 / 70 R 19.5, WTL 32
18 PR, 141 / 140 J, TL, 3PMSF
TR, Windpower

Product-No.: 10466454

Technical Information:

Product number	10466454
Tyre Size	245 / 70 R 19.5
R / D	Radial
TL / TT	TL
LI / SI	141 / 140 J
PR	18
Profile	WTL 32
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	7.50
Permissible rim	6.75
Width mm	253
Outer diameter mm	839
Static radius mm	433
Rolling circumference mm	2559
Payload in kg at kph (1)	2575 / 100
Inflation pressure bar	8,30
Weight kg	35,7
Rolling resistance	D
Wet grip	B
Rolling noise DB	71
Rolling noise level	A
Stud height mm	13,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nennbreite [mm]	245
Querschnittsverhältnis	70