Bohnenkamp Moving Professionals

WIND? WER



Hints and features:

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.

Dæk 205 / 75 R 17.5, WSR 24 14 PR, 124 / 122 M, TL, 3PMSF VA, Windpower

Product-No.: 10466466

Technical Information:

Product number	10466466
Tyre Size	205 / 75 R 17.5
R / D	Radial
TL / TT	TL
LI / SI	124 / 122 M
PR	14
Profile	WSR 24
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	6.00
Permissible rim	6.75, 7.50
Width mm	206
Outer diameter mm	752
Static radius mm	352
Rolling circumference mm	2294
Payload in kg at kph (1)	1600 / 130
Inflation pressure bar	7,60
Weight kg	27,6
Rolling resistance	D
Wet grip	В
Rolling noise DB	73
Rolling noise level	В
Stud height mm	13,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nennbreite [mm]	205
Querschnittsverhältnis	75
Profilsymmetrie	symmetrisk

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.