





Hints and features:

- All-purpose implement tyre.
- The grooved tread pattern is suitable for use on agricultural trailers, seeders and balers

Dæk 3.00 - 4, K406 4 PR, 34 A4 / 45 A4, TT (100/90-4), 3 Rib, med slange, Kenda

Product-No.: 19211070

Technical Information:

Product number	19211070
Tyre Size	3.00 - 4
R/D	Diagonal
TL/TT	TT
LI/SI	34 A4 / 45 A4
PR	4
Profile	K406
Manufacturer	Kenda
Specification	inkl. slange
Recom. Rim	2.10
Width mm	83
Outer diameter mm	260
Rolling circumference mm	776
Payload in kg at kph (1)	118 / 20
Payload in kg at kph (2)	165 / 20
Inflation pressure bar	3,30
Weight kg	0,91
Certified	ECE 106
Managhasita [7all]	
Nennbreite [Zoll]	3.00

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.