Bohnenkamp Moving Professionals



Hints and features:

- The Kargomax ST-6000 is a tyre for car trailers and caravans
- This tyre represents a perfect synthesis of traction, comfort and durability
- The newly-developed rubber compound ensures high mileage and low rolling resistance
- These tyres are approved exclusively for trailer usage

Dæk 155 R 13 C, KargoMax ST 6000 91 / 89 N, TL, M+S (155/80R13), GT Radial

Product-No.: 19866010

Technical Information:

Product number	19866010
Tyre Size	155 R 13 C
R / D	Radial
TL / TT	TL
LI / SI	91 / 89 N
Profile	KargoMax ST 6000
Manufacturer	GT Radial
Specification	M+S
Recom. Rim	4.50B
Permissible rim	4.00B, 4J, 4.50J, 5.00B, 5J
Width mm	157
Outer diameter mm	578
Static radius mm	262
Rolling circumference mm	1763
Payload in kg at kph (1)	615 / 140
Inflation pressure bar	4,50
Weight kg	5,92
Rolling resistance	С
Wet grip	С
Rolling noise DB	70
Rolling noise level	В
Certified	ECE 54, ECE 117
M+S	M+S
Nennbreite [mm]	155
Commercial van mark	С
Profilsymmetrie	symmetrisk

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.