

BRIDGESTONE



Hints and features:

- The Bridgestone M-40B was designed for mowers
- It provides good traction and better grip on slopes
- Its tread pattern protects soil and prevents damage to turf

Dæk 24 x 8.50 - 12, M40B 4 PR, 78 A6, TL Bridgestone

Product-No.: 10691215

Technical Information:

Product number	10691215
Tyre Size	24 x 8.50 - 12
R/D	Diagonal
TL/TT	TL
LI/SI	78 A6
PR	4
Profile	M40B
Manufacturer	Bridgestone
Recom. Rim	7JA
Width mm	222
Outer diameter mm	620
Static radius mm	285
Rolling circumference mm	1826
Payload in kg at kph (1)	425 / 30
Payload in kg at kph (2)	550 / 15
Inflation pressure bar	1,60
Weight kg	8
Stud height mm	6,0
Certified	ikke nødvendigt
Nennbreite [Zoll]	8.50
Nennaußendurchmesser [Zoll]	24
Profilsymmetrie	symmetrisk

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp A/S does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.